

Request For Quotation

| | |
|--|---|
| Description | : RFQ-001747 - Paint Work of Circular MS Columns of Library |
| Date of Issue | : 26 Mar 2024 |
| Date of Submission of Quotation | : 29 Mar 2024 11:00:00 AM |
| Place of Delivery | : Stores, IBA Main Campus, University Road, Karachi. |
| Contact Person & Telephone | : Purchase Department IBA Main Campus, University Road, Karachi. 03122669895 Extension : 2150 |

| Sr# | Description | Quantity + UOM |
|-----|--|----------------|
| 1 | <p>Painting Surface Preparation The surface to be over-coated must be dry and free from surface contaminants. Completely remove the old paint from the surface and sand down the surface by using sand paper thoroughly to ensure a smooth finish to Remove all previous paint, dust and residues completely before commencing painting. Apply Gelaso Soft Sanding Fast Body Filler grey Polyester Putty where necessary complete in all respect.</p> | 3100 SFT |
| 2 | <p>Epoxy Paint Finish Supply and apply one coat of primer and two coats Metal Epoxy paint finish of Master Paints or equivalent or approved quality on MS Columns & other structure by using Airless Spray in approved shades, prior to application all surface generally must be clean, dry, free from all defective or poorly adhering material, dirt, and grease etc, complete in all respect as directed by Engineer and as per manufacturer's recommendations. Airless Spray tip 13 thou, 2000 psi Epoxy Paint should be applied over a suitable primer or build coat. For recoating, the underlying system should be intact, sound and undamaged. Ensure that the surface to be over-coated is clean, dry, free from dust, grease and oil, or any other surface contaminants. Wash surface using fresh water to remove soluble salts. Always ensure to follow the maximum over-coating time for the primer/build coat and it should not be exceeded prior to application. Suitable Primers: Master Epoxy Z.P Primer or equivalent</p> | 3100 SFT |
| 3 | <p>Distemping & Painting Repainting two (2) coats of Matt Enamel paint of Berger, (ICI) Dulux, GOBIS or equivalent of approved make and shade to walls & ceiling, besides the two coats of paints, prior to application wall putty must be applied where necessary, all surface must be clean, dry, free from all defective or poorly adhering material, dirt, generally and grease etc, complete in all respect as per specification</p> | 1000 SFT |

Terms & Conditions :

1. Material of this order is subject to final inspection at the time of delivery.
2. We reserve the right to cancel any or all the above items if material is not in accordance with our specification or if the delivery is delayed.
3. Payment will be made through crossed cheque after the receipt of the Invoice/Bill & delivery of above item(s).
4. General Sales Tax will be paid on applicable items only.
5. Liquidity damage at the rate of 2% per month on actual will be imposed on delayed delivery.
6. The rate I item cost is final and no change what so ever will be accepted.



7. Government tax(es), levi(es) and charge(s) will be charged at actual as per SRO.
8. Competent Authority reserves the right to change/ alter I remove any item or article or reduce I enhance quantity without assigning any reason.
9. Invoice/Bill to be submitted to Purchase Department.
10. Advance Payment subject to Bank Guarantee.
11. All Government taxes (including Income tax and stamp duty), levies and charges will be charged as per applicable rates I denomination of Purchase Order.
12. Stamp Duty 0.35% for Goods against total value of Purchase Order will be levied accordingly.