

Institute of Business Administration (IBA)

Main Campus

BOQ of DATA CENTER FURNITURE, NBP BUILDING

Dated: 22-Feb-2023

RENOVATION WORK AT NBP BUILDING

Bill of Quantity

1. Item No.	2. Description of Item	3. Quantity	4. Unit
1	<p><u>Low Height Partition (Semi Glazed)</u> Providing and fixing in position partly glazed 4'-0" HT. Partition work as per drawing using partial wood frame work of 1.5 inch (thick) and 2 inch (wide) (horizontally and vertically) with 20 mm MDF laminated sheets on both sides finished of approved shade and colour as shown in drawings. Item to include 5 mm thick glass of 1'-0" height with frosted paper both sides and fitted with 1.5" thick partial wood frame. All exposed wood surfaces to be finished wood polish of approved shades as directed including all necessary fittings/hardware and wood preservative (termite proofing) etc. as per list of approved material and as approved by the Engineer Incharge complete in all respects.</p>	100.0	Sft.
2	<p><u>Fabricate & Supply Office Table</u> Fabricate & Supply Office Table with Top (4' x 2' x 3/4") As per the attached Drawing & approved sample Table Specification: • Top: 4' x 2' x 3/4" (thick) made of high-pressure both sides laminated (Tuff Formica) pressed on particle board • 2 mm thick PVC lipping • Resting on two legs from one side & resting on Cabinet on the other side. • Legs & Table Supports: Ash-White Powder-Coated MS Pipe 2" x 1/2", Wall thickness: 3 mm</p>	2.0	Each
3	<p><u>Fabricate & Supply Side Table (1'-5" x 2'-2" x 1'-9")</u> Cabinet Specification: • Made up of 20 mm (3/4") thick Oak ply laminated MDF Sheet on top, sides, bottom, shelves, and shutters • 6 mm thick marine ply at the back • Box-type hinges of approved make • Teak Lipping finished with melamine of approved laminate on all the shutter edges. • External surfaces finished with 1 mm thick Laminate of approved make • 20 mm thick Oak Ply laminated shelves of 16" wide and dividers as per drawing (approx./divided equally) • Complete with all necessary approved fittings hinges, locks, 150 mm long SS brush-finished handles, tower bolts, etc.</p>	2.0	Each
4	<p><u>Fabricate & Supply Wall Cabinet (3'-6" x 1'-1" x 2'-1")</u> Cabinet Specification: • Made up of 20 mm (3/4") thick Oak ply laminated MDF Sheet on top, sides, bottom, shelves, and shutters • 6 mm thick marine ply at the back • Box-type hinges of approved make • Teak Lipping finished with melamine of approved laminate on all the shutter edges. • External surfaces finished with 1 mm thick Laminate of approved make • 20 mm thick Oak Ply laminated shelves of 16" wide and dividers as per drawing (approx./divided equally) • Complete with all necessary approved fittings hinges, locks, 150 mm long SS brush-finished handles, tower bolts, etc.</p>	2.0	Each