

6. Bill of QuantitySCOPE OF WORKWaterproofing Works in G&T Auditorium and Library

S#	Description	Unit	Quantity	Rate	Amount
1	<b>Roof Treatment By EXPANCOTE RUBBER-FLEX</b>  PROVIDING & APPLYING EXPAN COTE RUBBER-FLEX MANUFACTURED BY FOS PAK CONFIRMING TO ASTM D- 543 AND ASTM C- 907 or equivalent as approved. The material is to be applied as per application procedure prescribed by the manufacturer by qualified / specialized applicator. Application: ExpanCOTE* Rubber-flex should be applied by brush, roller, trowel or spray (Two coats application on horizontal surfaces) at a minimum wet film thickness of 1.0 mm On a vertical surface a film build of 1.5 – 2.50 mm is achievable in two to three coats with reinforced polyester sheet. This rate is inclusive of all type of labour, material, tools & plants, Scaffolding , lifting, testing of surface as per prescribed etc. This rate is also inclusive of all type of federal, provincial and municipal taxes etc. complete. <b>Note:</b> Existing waterproofing material shall be removed and shifted from the surface first. Proper surface preparation and approval must be achieved prior application of coat. <b>Note:</b> Minimum one year of warranty shall be given by Contractor for waterproofing material.	25,810	Sft	78.00	2013180.9
2	<b>Cement Screed C-20 (1:2:4)</b>  Supply, mix, place compact and cure concrete C-20 (1:2:4) , screed to roof with Duracrete Fibers ( 300 gm / Bag of cement) or equivalent required slope and profile, including sump at drain points as shown on detailed drawing with smooth trowel finish, concrete to be laid in panels not exceeding 2000x2000mm including fillet 100 x 100mm along walls / beams and columns, complete	1,022	Sft	142.00	145124

Syed Atiq Hussain Kazmi  
Member - PC  
Manager Finance (Payable)  
IBA Karachi

SYED WAHEEH ZAHEDI  
Member - PC  
Sr. Manager IT  
IBA Karachi

DR. SHAHID MIR  
Chairman PC  
Assistant Professor - Management  
IBA Karachi



	in all respect, specification and as directed by the Engineer. 50 mm ( 2 inch.) thick Avg.				
3	<b>Making of 4" x 4" P.C.C Chamfer</b> Cutting, making rough chamfer 4" x 4" in triangular at wall and roof joint all along the sides of the building and making Cahmfer 4" x 4" using concrete ratio 1: 1.5 : 3 having 3/4" ( 20 mm ) down crush including using of S.B.R , curing etc complete in all respect as directed by Engineer Incharge.	875	Rft	23.00	128250
4	<b>Expanded Metal MS Jali 16 SWG</b> 'Supply and fixed Galvanized Expanded Metal MS Jali 16 SWG of (1" x 1") Diamond size in Standard Diamond Orientation or Reversed Diamond Orientation galvanized, fixed with 2" thick Steel nails and washer all around the corners inclusive of all tools and plants, complete in all respect as directed by Engineer Incharge.	1,022	Sft	110.00	112420
<b>Total Amount</b>					
<b>13% SST</b>					
<b>Grand Total Amount</b>					2296974

Grand Total Amount Rupees in Words: Rs. \_\_\_\_\_

DR. SHAHID MIR  
Chairman PC  
Assistant Professor - Management  
IBA Karachi

Syed Akbar Hussain Kalami  
Member - PC  
Manager Finance (Payable)  
IBA Karachi

M. H. ARIS QURESHI  
External Member - PC  
Procurement Specialist - HEJ  
University of Karachi

SYED WAJEEH ZAIDI  
Member - PC  
Sr. Manager IT  
IBA Karachi



Stamp &amp; Signature