

Bill of Quantity
IT Room Raise Flooring

S.NO	DESCRIPTION	ITEM DESCRIPTION	UOM	QTY
01	Raised Access Flooring System	Providing of Anti-Static Raised Floor CONCORDE SOLUTIONS / MERO GERMANY consisting of 38mm thick panels (600mmx600mm), composed of High Density Partical board in sandwich construction, approved finish on top and steel on the panel underside, full depth ABS edge band applied creating a fully encapsulated panel. FFH 300mm	SQFT	92
		Panel Size: 600x600 mm		
		Panel thickness: (no covering): 38 mm		
		Panel bottom side: galvanized steel sheet aluminum foil without coating		
		System weight: ~ 59 - 95 kg/m ²		
		Panel weight: ~ 18 - 26 kg/unit		
		FIRE PROTECTION		
		Building material class acc. to DIN EN 13501 T1: A1		
		FIRE RESISTANCE CLASS		
		acc. to DIN 4102 T2: F30 possible		
		acc. to DIN EN 1366-6: REI30 possible		
Including With precision steel pedestals, PVC Skirting and Accessories				
2	Cable Raceway	Data & Fiber Cable Raceway Size: WxDxG 305mmx152mmx18G Perforated Steel Powder Coated Orange with 2inch Feet's (without Cover)	RFT	20
3	Cable Ties	Nylon cable Ties CV-250M,250X3.6,Black Pcs 200	EACH	2
4	Cable Manager	3M Front Cable Manager – Plastic Black Body	EACH	2
5	SERVICES	LABOUR CHARGES CABLE LAYING Job Including UTP Cable Laying + Back Bone laying + back box I/O & RJ45 Termination + Rack Harnessing + Channel Duct laying & Fixing +, Tagging.	JOB	1