



IBA Institute of
Business Administration
Karachi

Leadership and Ideas for Tomorrow

PURCHASE ORDER

To : M/s Digital Links (Pvt) Ltd
Order No : IBA-MC/PD/P&S/205/0079/2015-16
Date of Issue : November 25, 2015
Date of Delivery : December 8, 2015
Place of Delivery : IBA, Main Campus
Total Amount : **Rs.1,250,782.65 (Including GST)**
(Rupees One Million Two Hundred Fifty Thousand Seven Hundred Eighty Two & Paisa Sixty Five Only)

S. #	DESCRIPTION	QTY	RATE (RS.)	AMOUNT (RS.)
	<u>IP CAMERA- MINI DOME - 1.3 MP HIK VISION</u>			
1	<ol style="list-style-type: none">Support dual stream, and the sub-stream for mobile surveillanceHigh-performance and long service life infrared LED. Approx. 10 to 30 meters IR rangeMust Support intrusion detection, line crossing detectionMust Support VCA, which is compatible with NVR for the second time of video searching and analyzingUp to 1.3 megapixel (1280 × 960) resolutionWi-Fi SupportStandard video compression with high compression ratio, ROI (region of interest) encodingProgressive scan CMOS, capture motion video without incised marginBuilt-in Micro SD/SDHC/SDXC card slot, up to 128 GBIngress Protection level: IP66Two-way audio SupportAudio Support Input OutputIR cut filter with auto switchPoE (Power over Ethernet)Impact Protection: IEC60068-2-75 test, Eh, 20J; EN50102, up to 1K10Other functions: rotate mode, alarm, mirror, reset button, etcImage Sensor: 1/3" Progressive Scan CMOSMin. Illumination: 0.01Lux @ (F1.2, AGC ON), 0 Lux with IR, 0.028 Lux @ (F2.0, AGC ON), 0 Lux with IRShutter Speed: 1/3 s to 1/100,000 sLens: Angle of view: 92.5°@2.8mm LENS	42 units	Rs.14,435.00	Rs.606,270.00

21. Lens Mount: M12
22. Day & Night: IR cut filter with auto switch
23. Digital Noise Reduction: 3D DNR
24. Wide Dynamic Range: Digital WDR
25. Angle Adjustment: Pan: 0° - 355°
Tilt: 0° - 75°, Rotation: 0-355°
26. Video Compression: H.264+
27. H.264 Type: Main Profile
28. Video Bit Rate: 32 Kbps - 12 Mbps
29. Dual Stream: Yes
30. Audio Compression: G.711/G.722.1/G.726/MP2L2
31. Audio Bit Rate: 64Kbps(G.711)
16Kbps(G.722.1)/16Kbps(G.726)/32-
128Kbps(MP2L2)
32. Max. Resolution: 1280 x 960
33. Frame Rate: 50 Hz; 25 fps (1280
x 960), 25 fps (1280 x 720)
60 Hz; 30 fps (1280 x 960), 30 fps (1280 x
720)
34. Image Settings: Rotate mode, Saturation,
Brightness, Contrast adjustable
by client software or web browser
35. Backlight compensation: Yes, zone
optional
36. ROI: (Region of interest) Support
37. Line crossing Detection Support
38. Network Storage: Local storage: Built-in
Micro SD/SDHC/SDXC card slot, up to
128 GB.
39. NAS: Must Supported NAS (Support NFS,
SMB/CIFS)
40. Protocol: TCP/IP, ICMP, HTTP, HTTPS, FTP, D
HCP, DNS, DDNS
RTP, RTSP, RTCP, PPPoE, NTP, UPnP,
SMTP, SNMP
PPPoE, NTP, UPnP, SMTP, SNMP, IGMP
802.1X, QoS, IPv6, Bonjour
41. Standard: ONVIF, PSIA, CGI, ISAPI
42. Communication Interface: 1 RJ45
10M/100M Ethernet interface
43. Alarm interface: 1 alarm I/O
44. Audio interface: 1 audio I/O
45. Wireless Standards:
IEEE802.11b, 802.11g, 802.11n
46. Frequency Range: 2.4 GHz - 2.4835
GHz
47. Channel Bandwidth: 20/40MHz Support
48. Protocols: 802.11b: CCK, QPSK,
BPSK
49. 802.11g/n: OFDM
50. Security: 64/128-bit WEP,
WPA/WPA2, WPA-PSK/WPA2-PSK, WPS
51. Transmit Output Power: 11b:
17±1.5dBm @ 11Mbps
11g: 14±1.5dBm @ 54Mbps
11n: 12.5±1.5dBm

	<p>52. Receive Sensitivity: 11b: -90dBm @ 11Mbps (Typical) 11g: -75dBm @ 54Mbps (Typical) 11n: -74dBm (Typical)</p> <p>53. Transfer Rates: 11b: 11Mbps 11g: 54Mbps 11n: up to 150Mbps</p> <p>54. Wireless Range: 50m (minimum)</p> <p>55. Wireless Standards: IEEE802.11b, 802.11g, 802.11n</p> <p>56. Operating Conditions: -30 °C – 60 °C (-22 °F – 140 °F)</p> <p>57. Humidity: 95% or less (non-condensing)</p> <p>58. Power Supply: 12 V DC \pm 10%</p> <p>59. PoE: (802.3af)</p> <p>60. Power Consumption: Max. 5W</p> <p>61. Ingress Protection level: IP66</p> <p>62. IR Range: 30 meters</p> <p>63. Impact Protection: IEC60068-2-75Eh, 20J; EN50102, up to IK10</p> <p>64. Dimensions: $\Phi 111 \times 82$ (4.4" \times 3.2")</p> <p>65. Weight: 500g (1.1 lb)</p> <p>65. Alarm Trigger: Line Crossing, Intrusion Detection, Motion detection, Dynamic analysis, Tampering, alarm. One-key reset, Network disconnect, IP address conflict, Storage exception, Flash-prevention, dual stream, heartbeat, mirror, password protection, privacy mask, watermark, IP address filtering.</p> <p>66. The camera Box should include following items:- a. IP Camera b. Power Adaptor 220 v c. Screw driver L Key type for camera d. Weather proof network connector cover e. Camera manual f. Packing</p> <p>67. Power supply should be included on each camera.</p>			
2	<p><u>NVR – 32 channel HIK VISION</u></p> <ol style="list-style-type: none"> Connectable to the third-party network cameras like like ACTI, Arecont, AXIS, Bosch, Brickcom, Canon, ONVIF, PANASONIC, Pelco, PSIA, SAMSUNG, SANYO, SONY and Vivotek and ZAVIO. Video Content Analysis: NVR Should support VCA for smart search Stream Media Server: NVR should support Stream Media Server to increase the number of users on Network or to decrease the load 	05 units	Rs.68,750.00	Rs.343,750.00

	<p>over WAN connection for multiple users at remote location</p> <ol style="list-style-type: none"> 4. Up to 64 network cameras can be connected 5. Support live view, storage, and playback of the connected camera with up to the resolution of 5 megapixels. 6. Simultaneous HDMI and VGA at 1920 × 1080 resolution. 7. New GUI and support starting record with one key; 8. Redundant recording, holiday recording and capture schedule configuration; 9. Realize instant playback for assigned channel during multi-channel display mode. 10. Up to 16-ch synchronous playback at 4CIF resolution. 11. Smart search for the selected area in the video. 12. Customization of tags, searching, and playing back by tags. 13. Locking and unlocking record files. 14. Compression: "H.264+" (NVR Should not be H.264 or below) 15. Support HDD quota and group modes; different capacity can be assigned to different channel. 16. Up to 4 SATA hard disks and 1 eSATA disk can be connected, for both recording and backup. 17. 1 self-adaptive 10M/100M/1000M network interface. 18. Support Hikvision DDNS (Dynamic Domain Name System); 19. Must Support Channel-zero encoding, which enables you to get a view in the remote client or web browser of all the channels in one screen. 20. Support network detection, including network delay, packet loss, etc. 21. Adopt pioneering dual-OS design to ensure the security of system running. 22. Channel Zero: NVR Should Support Channel Zero function with VBR function i.e. (32Kbps ~ 2Mbps) which sucks one camera bandwidth and shows at most 16-cameras View at a time 23. VGA/HDMI or CVBS: NVR should independently operate (VGA/HDMI) & CVBS 24. IP video/Audio input : 32-ch 25. Two-way audio: 1-ch, BNC (2.0 Vp-p, 1kΩ) 26. Incoming bandwidth: 160Mbps 27. Outgoing bandwidth: 160Mbps 28. Remote Connection: 128 29. Video/Audio output: 32 30. Recording resolution 5MP /3MP /1080P/UXGA /720P /VGA /4CIF /DCIF /2CIF /CIF /QCIF 31. Compression: "H.264+" (NVR Should not be H.264 or below) 32. Channel Zero: NVR Should Support Channel 			
--	---	--	--	--

	Zero function with VBR ability i.e. (32Kbps ~ 2Mbps) which sucks one camera bandwidth and shows at most 16-cameras View at a time		
33.	VGA/HDMI or CVBS: NVR should independently operate (VGA/HDMI) & CVBS		
34.	Video Content Analysis: NVR Should support VCA for smart search		
35.	Stream Media Server: NVR should support Stream Media Server to increase the number of users on Network or to decrease the load over WAN connection for multiple users at remote location		
36.	NAS: NVR should support NAS function		
37.	Frame rate: Main stream: 25 fps (P) / 30 fps (N) 1. Sub-stream: 25 fps (P) / 30 fps (N)		
38.	CVBS output: 1-ch, BNC (1.0 Vp-p, 75 Ω)		
39.	Resolution: 704 \times 576 (PAL); 704 \times 480 (NTSC)		
40.	HDMI output: 1-ch, resolution: 1920 \times 1080P /60Hz, 1920 \times 1080P /50Hz, 1600 \times 1200 /60Hz, 1280 \times 1024 /60Hz, 1280 \times 720 /60Hz, 1024 \times 768 /60Hz		
41.	VGA output: 1-ch, resolution: 1920 \times 1080P /60Hz, 1600 \times 1200 /60Hz, 1280 \times 1024 /60Hz, 1280 \times 720 /60Hz, 1024 \times 768 /60Hz		
42.	Audio output: 2-ch, BNC (Linear, 600 Ω)		
43.	Playback resolution 5MP /3MP /1080P /UXGA /720P /VGA /4CIF /DCIF /2CIF /CIF /QCIF		
44.	Synchronous playback: 16-ch		
45.	Hard disk (SATA) 4 SATA interfaces		
46.	eSATA 1 eSATA interface		
47.	Capacity: Up to 4TB capacity for each HDD		
48.	Network interface: 1 RJ-45 10 /100 /1000 Mbps self-adaptive Ethernet		
49.	Serial interface: RS-232; RS-485; Keyboard		
50.	USB interface: 3 \times USB 2.0		
51.	Alarm in: 16		
52.	Alarm out: 4		
53.	Power supply: 100 ~ 240 VAC, 6.3 A, 50 ~ 60 Hz		
54.	Power Consumption: (without hard disk) \leq 45 W		
55.	Working temperature: -10 $^{\circ}$ C ~ +55 $^{\circ}$ C		
56.	Working humidity: 10 % ~ 90 %		
57.	Chassis 19-inch rack-mounted 1.5U chassis		
58.	Dimensions (W \times D \times H) 445 \times 390 \times 70 mm		
59.	Weight \leq 4 Kg (8.82 lb) (without hard disk)		

3	<u>LED- 32 channel SAMSUNG</u>			
	Display Technology LED			
	1.2D/3D	2D		
	2.Internet Enabled	No		
	3.Refresh Rate	EMR 120Hz		
	4.Aspect Ratio	16:9		
	5.Resolution	720p or higher		
	6.Energy Grade	Energy Star		
	7.Category	LED TV		
	8.Brightness (cd/m2)	250		
	9.Contrast Ratio	1200:1 or better		
	10. Response Time	6.5ms		
	11. Viewing Angle (H/V)	170°/170°		
	12. Life Time	>30,000hrs (min)		
	13. Colors	16.7M	3 unit	Rs.39,675.00
	14. Speakers	Integrated speakers		Rs.119,025.00
	(Bottom side)			
	15. Audio Power Output	5W+5W		
	16. SRS True Surround HD	Yes		
	17. HDMI	2		
	18. USB	1		
	19. AV in	1		
	20. AV out	1		
	21. RF	1		
	22. Component (Y/Pb/Pr)	1		
	23. VGA	1		
	24. SPDIF	Coaxial		
	25. 3D Glasses	No		
	26. Power Supply	AC 220V 50/60Hz		
	27. Power Consumption - TV on	50W		
	28. Power Consumption - Standby	<0.5W		
Total			Rs.1,069,045.00	
17% GST			Rs.181,737.65	
Total Amount			Rs.1,250,782.65	

General Instructions:-

- All the items should be available in ready stock and displayed in front of the end user.
- No un marked items acceptable
- No Neutral version and Chinese version acceptable.
- Supplier should have office located in Karachi.
- Items should have local warranty.

Terms & Conditions:

1. Material of this order is subject to final inspection at the time of delivery.
2. We reserve the right to cancel any or all the above items if material is not in accordance with our specification or if the delivery is delayed.
3. Payment will be made through crossed cheque after the receipt of the bill and delivery of the above item.
4. General Sales Tax will be paid on applicable items only.
5. Penalty at the rate of 2% per month on actual will be imposed on delayed delivery.
6. The rate / item cost is final and no change what so ever will be accepted.
7. Government tax(es), levi(es) and charge(s) will be charged at actual as per SRO.
8. Competent Authority reserves the right to change / alter / remove any item or article or reduce / enhance quantity without assigning any reason.
9. Invoice / bill, Purchase Order & Delivery Challan should be submitted to Finance Department.
10. Advance Payment subject to Bank Guarantee
11. All Government taxes (including Income tax and stamp duty), levies and charges will be charged as per applicable rates / denomination of Purchase / Work Order.
12. Stamp duty 0.35% for Goods against total value of Purchase Order will be levied accordingly.



Manager Purchase & Stores

Nov 25/15



Registrar