# **Institute of Business Administration (IBA)**

## **Main Campus**

## BOQ OF Wooden Partition & Crdenza Cabinet in Testing Office

#### RENOVATION WORK AT TESTING OFFICE, FAUJI BUILDING

1. Item No.	2. Description of Item	3. Quantity	4. Unit
1	LOW HEIGHT Partition  Providing and fixing in position 3'-0" HT. Wooden Partition work as per drawing using partal wood frame work of 1.5 inch (thick) and 2 inch wide (divided 24" horizontally and 18" vertically) with 16 mm MDF laminated sheets of ZRK or Al-Noor brand or Equivalent on both sides finished of approved shade and colour as shown in drawings with Lipping. Provide 4" wide Aluminium skirting at the bottom of partition on both side.All exposed wood surfaces to be finished with wood lacquer polish and necessary lipping (Upto 12 mm thick Partal Wood) of approved shades as directed including all necessary fittings/hardware and wood preservative (Termite Proofing) etc. as per list of approved material and as approved by the Engineer Incharge complete in all respects.	105.0	Sft.
2	MDF Laminated TABLE TOP  Providing and fixing in position 16 mm thick Table top (Size as per drawing) using 16 mm MDF laminated sheets of ZRK or Al-Noor brand or Equivalent of approved shade and colour with front gola to be 38mm thick (size: 38mm x 38mm) with PVC lipping of same color/texture as shown in drawings. The sides & bottom of table top shall be covered by Partal wood frame (1.5" x 2") for support. All exposed wood surfaces to be finished with necessary wooden beeding (5mm thick Partal Wood) with lacquer polish as directed including all necessary fittings/hardware and wood preservative (Termite Proofing) etc. as per list of approved material and as approved by the Engineer Incharge complete in all respects.	80.0	Sft.
3	Mobile Cabinet (1'-8"x 1'-8"x2'-5") Cabinet Specification:  • Made up of 20 mm (³/₄") thick Dull White MDF laminated Sheet of ZRK Brand or Equivalent on top, sides, bottom, shelves, and shutters • 6 mm thick marine ply at the back • Box-type hinges of approved make • PVC Lipping finished with melamine of approved laminate on all the shutter edges. • 20 mm thick Dull White MDF laminated shelves, width & depth shall be as per drawing • Complete with all necessary approved hardware, fittings hinges, locks of KHAS or Equivalent, 150 mm long SS brush-finished handles, tower bolts, etc. • Upto 2" Partal Wood frame • Providing of Drawer channels for smooth operation of drawer.	5.0	Each

# **Institute of Business Administration (IBA)**

## **Main Campus**

### BOQ OF Wooden Partition & Crdenza Cabinet in Testing Office

#### RENOVATION WORK AT TESTING OFFICE, FAUJI BUILDING

1.	2.	3.	4.
Item	Description of Item	Quantity	Unit
No.			
4	Credenza Cabinet ( 3'-6"x 1'-4"x2'-4") Cabinet Specification:  • Made up of 20 mm (¾") thick Dull White MDF laminated Sheet of ZRK Brand or Equivalent on top, sides, bottom, shelves, and shutters  • 6 mm thick marine ply at the back  • Box-type hinges of approved make  • PVC Lipping finished with melamine of approved laminate on all the shutter edges.  • 20 mm thick Dull White MDF laminated shelves, width & depth shall be as per drawing (approx./divided equally)  • Complete with all necessary approved hardware, fittings hinges, locks of KHAS or Equivalent, 150 mm long SS brush-finished handles, tower bolts, etc.  • Upto 2" Partal Wood frame  Note:  -Site Visit is mandatory before submission of quotationSST 13% will charge	2.0	Each