3.

BILL OF QUANTITY

S.#	permention	Quoted Brand	Quoted Model	Qty	Rate	Amount
1	Amplifier 70A A-1724 (AVALABLE TO OUR DISTRIBUTOR Description: TOA A-1712 or equivalent Mixer Power			07 sets	85,333/=	597,331/=
	Equipped with 6 Microphone inputs and 5 AUX inputs (simultaneous use of 9 inputs possible), the A-1712 PA amplifier of 120 W is designed to suit the following PA system applications: announcements, BGM, and broadcasting in mosques, churches, large rooms, and factories. Specification * 0 dB = 1 V Power Source 220 - 230 V AC, 50/60 Hz Rated Output 120 W Power/Current Consumption 258 W (rated output), 105 W (EN60065), 320 mA or less (when power switch is OFF) Frequency Response 50 Hz - 20 kHz (±3 dB) Distortion 2% or less at 1 kHz, rated power Input MIC 1 - 6: -60 dB*, 600, electronically-balanced, combined type of XLR-3-31 equivalent and phone jack AUX 1 - 2: -20 dB*, 600, electronically-balanced, combined type of XLR-3-31 equivalent adend phone jack (Either MIC 5 or AUX 1, and either MIC 6 or AUX 2 selectable) AUX 3 - 4: -20 dB*, 10 k, unbalanced, RCA pin jack AUX 5: -20 dB*, 10 k, unbalanced, combined type of XLR-3-31 equivalent and phone jack PWR AMP IN: 0 dB*, 600 ., unbalanced, RCA pin jack (An equalizer or other signal processor connectable between LINE OUT and PWR AMP IN terminals) Output REC: 0 dB*, 600 ., unbalanced, RCA pin jack LINE: 0 dB*, 600 ., unbalanced, RCA pin jack SPEAKER SELECTOR: 2 zone, high impedance (100 V line/83 .), individual selector key, M4 screw terminal DIRECT SPEAKER OUT: High impedance (100 V line/83 .), individual selector key, M4 screw terminal DIRECT SPEAKER OUT: High impedance (100 V line/83 .), individual selector key, M4 screw terminal DIRECT SPEAKER OUT: High impedance (100 V line/83 .), M4 screw terminal Both Low and High impedance terminals cannot be used at the same time.) Phantom Power ON or OFF for each MIC1 - 6 with switch setting (+17 V DC) S/N Ratio (Band Pass : 20 Hz - 20 kHz) 100 dB or more (Master			ENTRA P	THE COMMENT OF THE PROPERTY OF	in the state of th

CHAIRPERSON

CENTRAL PURCHASE COMMITTEE
INSTITUTE OF BUSINESS ADMINISTRATION
KARACHI

DR.S. M. Fuical Iraclal

As sistem Professor

IBA, Karachi

CENTRAL PURCHASE COMMITTEE MUTE OF BUSINESS ADMINISTRATION KARACHI

Haris Chreshi PARA Admisor HEJ

Page 5 of 12

17% GST 101 CA(1-	101,546/=	
Total 597, 331/=	597,331/=	
volume: min) 76 dB or more (Master volume: max) 60 dB or more (MIC 1 - MIC 4) 53 dB or more (MIC 5, MIC 6) 76 dB or more (AUX 1 - AUX 5) Tone Control Bass: ±10 dB at 100 Hz, Treble: ±10 dB at 10 kHz Control Input REMOTE VOLUME: M3 screw terminal POWER REMOTE: No-voltage make contact input, open voltage: 28 V DC (when the units power is OFF), short-circuit: 10 mA or less, M3 screw terminal Indicator 5 point LED output level meter, Power indicator LED, Zone indicator LED Operating Temperature -10 . to +40 . Finish Panel: ABS resin, black, hairline Case: Steel plate, black Dimensions 420 (W) × 107.7 (H) × 367 (D) mm Weight12.6 kg Accessory Power cord1, Terminal block cover mounting screw2 Option Rack mounting bracket: MB-25B Volume control cover: YA-920		

Total Amount Rupees (in words) Six LAC WINTY

EIGHT THOUSAND & EIGHT HUNDRED SEVENTY SEVEN ONLY

